

HEAVY DUTY OSCILLATING AIR CIRCULATOR

ONE OF AMERICA'S MOST POPULAR OSCILLATING MECHANISMS[†]

Thousands in use as a general circulation fan. This fan is ideal for providing general cooling in occupied open areas, such as staging areas, courtrooms, classrooms, and auditoriums.



Fan Performance

Tanre	nonnance				
Blade		Max	CFM		
Size	Fan Head	Amps	High	Low	
24"	LCHHD24O	3.1	6,000	4,500	
30"	LCHHD30O	3.3	7,600	5,000	
Motor		1/4 HP, 2-sp enclosed, th PSC motor v bricated ball	ermally p vith perm	protected, anently lu-	
Switch	า	Heavy duty	pull chair	1	
Cord		12' long 3 conductor SJT type			
Blade		Coated steel			
Guard		Powder coat finish			
Fan Head Tilt		Pedestal - 10° up or down Wall Mount - 10° up or down			
Column Adjustment		48-7/8 to 60 inches			
Pedestal base		27" diameter steel dome			
Column/Base Connect		5 carriage bolts			

Meets OSHA standards.

MEP recommends the use of safety cable model 2430SC with this fan when mounted on a wall, I-beam, ceiling mount. Safety cable included with I-beam, ceiling and suspension mounts.



Features a durable American-Made safety clutch style oscillating

mechanism. The fan may be set to operate at 90° or in a fixed position. The air circulator is available as a 24" or 30" Pedestal or Wall mounted fan. NOTE: Oscillating fan not to be used in upside down positions.

ordoning outlinary							
BLADE	FAN	ORDER N	ORDER NUMBER		SHIPPING WEIGHT		
SIZE	TYPE	FAN HEAD	MOUNT	HEAD	MOUNT		
24"	Head	LCHHD24O	—	41 lbs.	—		
24"	Pedestal	LCHHD24O	2430PB	41 lbs.	35 lbs.		
24"	Wall Mount	LCHHD24O	2430WG	41 lbs.	5 lbs.		
30"	Head	LCHHD30O	—	48 lbs.	_		
30"	Pedestal	LCHHD30O	2430PB	48 lbs.	35 lbs.		
30"	Wall Mount	LCHHD30O	2430WG	48 lbs.	5 lbs.		

NOTE: Air Circulator heads are factory assembled (motor, blade, and guard) and ship in one carton. Fan mounts ship in separate carton.

Optional Accessories

ТҮРЕ	ORDER NUMBER		
Wheel Kit	PBWK		
Safety Cable	2430SC		

† Based on sales over the past 25 years NOTE: LCHHD300 does not meet UPS shipping criteria LCHHDOBulletin