

THE LEADERS
IN INVISIBLE
HEAT SOLUTIONS







- Baseboard Heaters
- Wall Heaters
- Made-to-Spec Heaters
- Ceiling Heaters
- Unit Heaters
- Washdown/Explosion Proof Heaters
- Convactor Heaters
- Radiant Heaters
- Portable Heaters
- Thermostats & Controls
- Heat Recovery Ceiling Fans
- Air Curtains
- ... And More



Marley®
Engineered Products

INDUSTRIAL
LINE CARD

VENTILATION SOLUTIONS FOR
INDUSTRIAL APPLICATIONS









Marley®
Engineered Products

To see a more complete line of
products go to www.marleymep.com

Industrial Ventilation Solutions for Any Application

INDUSTRIAL VENTILATION SOLUTIONS

PEDESTAL & WALL FANS	BLOWERS	AIR CURTAINS	PORTABLE
<div>HEAVY DUTY 2 speed motor Up to 3 year warranty Available in 120V 2900 to 12550 CFM 1/4 to 1/2 HP motors</div> <div></div>	<div>BELT DRIVE 20 gauge steel housing Standard or tilt cart 36" to 48" 14,800 to 23,000 CFM High quality ODP motor</div> <div></div>	<div>LOW PROFILE Modern, contemporary design 120V and 240V Max velocity— 1800 FPM 36" to 60" Can mount end to end Stainless steel available</div> <div></div>	<div>POWER CAT Blower rotates 90 degrees Duct accessories available 300 to 1120 CFM 25' heavy duty grounded cord Duplex receptacles on front</div> <div></div>
<div>WALL 2 speed motor Up to 3 year warranty Available in 120V 2900 to 12550 CFM 1/4 to 1/2 HP motors</div> <div></div>	<div>DIRECT DRIVE 24 gauge steel housing Standard or tilt cart 30" to 48" 5,800 to 17,300 CFM 2 speed enclosed motor (select models)</div> <div></div>	<div>ENVIRONMENTAL Food service & commercial applications Smart-Trac mounting system No tools maintenance Max velocity— 2800 FPM 36" to 144"</div> <div></div>	<div>AIR HOG 8" or 12" diameter 1225 to 2450 CFM Easy carry handle Industrial grade power cord</div> <div></div>
<div>SPECIALTY USDA approved Specialty washdown 24" or 30" 5200 to 8600 CFM 1/3 HP motor</div> <div></div>	<div>SUSPENSION 20 gauge steel housing 30" to 42" 5,800 to 16,500 CFM 2 speed enclosed motor Hanging hardware included</div> <div></div>	<div>HIGH VELOCITY Approved for installation in a concealed space 18 gauge steel casing for rugged applications Single point field wiring 208V—1.9kW or 240V—2.5kW</div> <div></div>	<div>EXHAUST INDUSTRIAL</div> <div><div>LPE Both models have 120V totally enclosed motors LPEV model: Venturi mounted 12", 16", 22" blade size Use with or without shutter LPES model: Shutter mounted fan reduces installation time.</div><div></div></div>
<div>UTILITY 12" to 20" 1550 to 5950 CFM 3 speeds Single bolt mounting Sleeve bearing open drip proof motor</div> <div></div>	<div>HEAVY DUTY 18 pole 115V motor Permanently sealed double ball bearing motor 3/8 x 7 1/4" locking J-hook for installation White epoxy finish, brown and black models available</div> <div></div>	<div>AIR CURTAIN ALSO AVAILABLE WITH:<ul style="list-style-type: none">• Electric heat• Hot water/steam heat3 phase</div>	