

THE LEADERS  
IN CUSTOM  
HEAT SOLUTIONS

- Baseboard Heaters
- Wall Heaters
- Made-to-Order Heaters
- Ceiling Heaters
- Unit Heaters
- Washdown/Explosion Proof Heaters
- Convector Heaters
- Radiant Heaters
- Portable Heaters
- Thermostats & Controls
- Heat Recovery Ceiling Fans
- Air Curtains
- ... And More



To see a more complete line of  
products go to [www.marleymep.com](http://www.marleymep.com)



COMMERCIAL  
LINE CARD

ELECTRIC HEAT SOLUTIONS  
FOR ANY APPLICATION







# Electric Heat Solutions for Any Application

## COMMERCIAL SOLUTIONS

WALL HEAT	CONVECTOR/RADIANT	UNIT/DUCT HEATERS	PORTABLE	CEILING
 <p><b>ARTISAN™</b> Sleek modern design Digital touch screen LCD thermostat BMS compatible Energy efficiency with proportional heating 120V, 208V, 240V, 277V 540W to 4800W</p>	 <p><b>INFRARED</b> IR technology heats the object and not the air = energy savings Clean, energy-efficient alternative to propane/gas = no fumes Perfect for indoor/outdoor applications with multiple finishes and mounting options 120V-600V units available from 1.5kW-13.5kW</p>	 <p><b>MUH</b> 3kW - 50kW / 208V, 240V, 277V, 480V Horizontal and downflow capability Long directed heat throw Smooth quiet operation</p>	 <p><b>MEDH (DRAGON HEATER)</b> Portable electric high capacity blower heater for applications where open flame is not allowed Perfect for outdoor work areas or construction sites 208V, 240V, and 480V in 10kW to 30kW sizes</p>	 <p><b>CDF</b> Surface enclosure or recessed 3 adjustable airflow patterns Built in fan delay Automatic thermal cutout 208V, 240V, 277V up to 5kW</p>
 <p><b>SSHO SMART SERIES®</b> High output digital programmable touch screen BMS Compatible Instant heat where and when you need it 208V, 240V, 277V 1800W to 4000W</p>	 <p><b>PANEL HEAT</b> Easy to install and flexible application Gentle heat with no noise or maintenance needed Available in 120V, 208V, 240V, 277V, 347V Invisible heat— silk screening to match any panel</p>	 <p><b>CABINET</b> Use in hallways, entryways, classrooms &amp; hospitals—limitless applications Floor, ceiling or wall mounted Fully customizable for your unique application or stock units available</p>	 <p><b>QCH</b> Built-in power on/off switch. Thermal cutout to shut off heater in case of overheating Fan delay energizes fan motor only after elements 120V, 208V, 240V, 277V 1000W to 2000W</p>	 <p><b>QWD WASHDOWN</b> Corrosion resistant 304 stainless steel Totally enclosed motor Nema 4x junction box protects controls against water Automatic reset limit 120V, 208V, 240V, 277V, 480V, 600V 2-39kW</p>
 <p><b>AWH</b> BMS Compatible with relay Fan delay preventing cold air discharge Manual reset overheat protection Totally enclosed motor 120V, 208V, 240V, 277V 1500W to 4800W</p>	 <p><b>DBA/SHA</b> Selection, beauty, and performance—customizable for any decor and heating need Floor, wall, or pedestal mount with bottom or front inlet Built-in wireway and multiple entry points for ease of system installation Aluminum, 120V-600V, 200W to 7500W+</p>	 <p><b>DBSL</b> Slim, compact design customizable for any decor and heating need Floor, wall, or pedestal mount with bottom or front inlet Built-in wireway and multiple entry points for ease of system installation Aluminum, 120V-600V, 200W to 2500W+</p>		
 <p><b>CWH ARCHITECTURAL</b> Fast heat response, compact design Contemporary bar stock for optimized airflow Fan delay preventing cold air discharge 120V, 208V, 240V, 277V 500W to 2000W</p>	 <p><b>SLQDB</b> Compact, customizable design with 6" install height perfect for under the window, heat loss prevention Built-in wireway and multiple entry points for ease of system installation Aluminum, 120V-600V, 200W to 1880W+</p>	 <p><b>CPH, DSH, CSH, DPH</b> Perfect for under the window, heat loss prevention Floor, wall, or pedestal mount with bottom or front inlet Built-in wireway and multiple entry points for ease of system installation Steel, 120V-600V, 250W to 7500W</p>	 <p><b>DUCT HEATERS</b> Open coil and finned tube available Slip in or flanged installations Made to order for complete customization</p>	 <p><b>MWUH</b> Ceiling mount bracket for horizontal/vertical air throw Built-in thermostat (45-90F) Automatic fan delay Dual voltage (208V/240V), up to 7500W</p>