PDH Portable Electric Blower Heater



HEAVY-DUTY FINTUBE ELEMENT DESIGN – UNIFORM HEAT OUTPUT

CONTROL YOUR COMFORT BUILT-IN THERMOSTAT

- BUILT-IN SAFETY THERMAL CUTOUT
- SAFE OPERATION IN UNATTENDED AREAS
- SHIPPED FULLY ASSEMBLED

► APPLICATIONS INCLUDE:

 EXCELLENT CHOICE TO HEAT AREAS THAT ARE INDOORS AND ENCLOSED WITH CEILING HEIGHTS OF 15 FEET OR LESS.



SELECTION CHART							
CATALOG							SHIP
NUMBER	VOLTS	PHASE	WATTS	AMPS	BTU/HR	DIMENSIONS	WT
PDH1021A	240	1	10	41.7	34,120	40"H X 30"W X 24"D	65 lbs
PDH1021CKA	240	1	10	41.7	34,120	40"H X 30"W X 24"D	65 lbs
PDH1583A	208	3	15	41.8	51,180	40"H X 30"W X 24"D	65 lbs
PDH1521A	240	1	15	62.5	51,180	40"H X 30"W X 24"D	65 lbs
PDH1523A	240	3	15	36.3	51,180	40"H X 30"W X 24"D	65 lbs
PDH1543A	480	3	15	31.2	51,180	40"H X 30"W X 24"D	65 lbs
PDH3043A	480	3	30	36.3	102,360	40"H X 30"W X 24"D	75 lbs

Note: All models are factory wired for 3 phase operation. Models designated 1 and 3 phase can be field wired for single phase operation.

