

BDH SERIES

HIGH-TEMP ELECTRIC BLOWER



IDEAL SPACES

- Construction Sites
- Truck Docks
- Mining
- Oil/Gas Extraction
- Food Processing
- Textile Mills
- Paper Mills
- Printing Plants
- Chemical Plants
- Marinas

COLORS

- Red
- Custom (any color available for branding)

DIMENSIONS

- 40"H x 30"W x 24"D

9 LHK 2 1 2 SN 2 LT ISYL PYL K 2

- Can be operated unattended without risk of fire or need for refueling.
- ✓ No exhaust fumes or added moisture like with gas heaters
- ✓ Control comfort with built-in thermostat and safety thermal cutout
- ✓ Fan-only mode for air recirculation, fume exhaust or fresh air supply
- ✓ Single- and three-phase operation
- ✓ 10 in. pneumatic wheels MVLHZ' YHUZWWY[
- ✓ Thermostat selector switch
- ✓ Optional ceiling/wall bracket available MV] LYH[[S TV \UPUN
- ✓ Cord sets for power supply feed available PUJ SKLP[OZV L T K LS



1563&44)08/3&033&&3&/&0/-:56*130&&.73:8&50
130&&/)7&./54

BDH SERIES

HIGH-TEMP ELECTRIC BLOWER

MODELS & SPECIFICATIONS

| CATALOG NO. | UPC | KW | PHASES | VOLTS | AMPS | BTU/HR | TEMP RISE DEG F | DIMENSIONS (IN) | SHIP WT. (LBS.) | STATUS |
|-------------|-----------------|----|--------|-------|------|---------|-----------------|-----------------|-----------------|--------|
| BDH1021CKA | 6 85360 15258 5 | 10 | 1 | 240 | 41.7 | 34,120 | 35-88 | 40H x 30W x 24D | 65 | S |
| BDH1583A | 6 85360 15225 7 | 15 | 3 | 208 | 41.8 | 51,180 | 35-88 | 40H x 30W x 24D | 65 | NS |
| BDH1521A | 6 85360 15219 6 | 15 | 1 | 240 | 62.5 | 51,180 | 59-141 | 40H x 30W x 24D | 65 | NS |
| BDH1523A | 6 85360 15221 9 | 15 | 3 | 240 | 36.3 | 51,180 | 59-141 | 40H x 30W x 24D | 65 | NS |
| BDH1543A | 6 85360 15223 3 | 15 | 3 | 480 | 18.6 | 51,180 | 70-172 | 40H x 30W x 24D | 65 | S |
| BDH3043A | 6 85360 15227 1 | 30 | 3 | 480 | 36.3 | 102,360 | 70-172 | 40H x 30W x 24D | 75 | NS |

NOTE: BDH1021CKA includes cord & plug kit packaged inside heater carton. Status descriptions: S - Stock; NS - Non-Stock.

ACCESSORIES

| CATALOG NO. | UPC | KW | DESCRIPTION | SHIP WT. (LBS.) |
|-------------|-----------------|---------|--|-----------------|
| DHCWM | 6 85360 15212 7 | - | Ceiling and wall bracket can be used on all models | 20 |
| SCS25043 | 6 85360 15251 6 | 4/3 SO | DH1521A | 22 |
| SCS10063 | 6 85360 15250 9 | 6/3 SO | DH1021A (10ft long w/plug) | 18 |
| SCS25064 | 6 85360 15252 3 | 6/4 SO | DH1583A, DH1523A, DH3043A | 20 |
| SCS25124 | 6 85360 15253 0 | 12/4 SO | DH1543A | 10 |

CORD & PLUG KITS

| CATALOG NO. | KW | VOLTS | PHASE | AMPS | WIRE SIZE | 25 FT CORD SET | LOCKING | NON-LOCKING | SHIP WT. (LBS) |
|-------------|----|-------|-------|------|-----------|------------------|----------|-------------|----------------|
| BDH1021A | 10 | 240 | 1 | 39.6 | 6/3 | SCS10063 (10ft.) | - | INCLUDED | 18 |
| BDH1583A | 15 | 208 | 3 | 41.8 | 6/4 | SCS25064 | LPS25064 | - | 20 |
| BDH1521A | 15 | 240 | 1 | 62.5 | 4/3 | SCS25043 | - | - | 22 |
| BDH1523A | 15 | 240 | 3 | 36.3 | 6/4 | SCS25064 | LPS25064 | NPS1550 | 20 |
| BDH1543A | 15 | 480 | 1 | 31.2 | 6/4 | SCS25064 | LPS25064 | NPS1550 | 20 |
| | | | 3 | 18.1 | 12/4 | SCS25124 | LPS25104 | - | 10 |
| BDH3043A | 30 | 480 | 3 | 36.3 | 6/4 | SCS25064 | - | - | 20 |

NOTE: Models designated 1 and 3 phase can be field-wired for single-phase operation.