

# BDH SERIES

## HIGH-TEMP ELECTRIC BLOWER



### IDEAL SPACES

- Construction Sites
- Truck Docks
- Mining
- Oil/Gas Extraction
- Food Processing
- Textile Mills
- Paper Mills
- Printing Plants
- Chemical Plants
- Marinas

### COLORS

- Red
- Custom (any color available for branding)

### DIMENSIONS

- 40"H x 30"W x 24"D

- Can be operated unattended without risk of fire or need for refueling.
- No exhaust fumes or added moisture like with gas heaters
- Heavy-duty spiral fin tube metal sheath elements for uniform heat output
- Control comfort with built-in thermostat and safety thermal cutout
- Fan-only mode for air recirculation, fume exhaust or fresh air supply
- Single- and three-phase operation
- 10- in. pneumatic wheels
- Thermostat selector switch
- Optional ceiling/wall bracket available
- Cord sets for power supply feed available



# BDH SERIES

## HIGH-TEMP ELECTRIC BLOWER

### MODELS & SPECIFICATIONS

CATALOG NO.	UPC	KW	PHASES	VOLTS	AMPS	BTU/HR	TEMP RISE DEG F	DIMENSIONS (IN)	SHIP WT. (LBS.)	STATUS
BDH1021CKA	6 85360 15258 5	10	1	240	41.7	34,120	35-88	40H x 30W x 24D	65	S
BDH1583A	6 85360 15225 7	15	3	208	41.8	51,180	35-88	40H x 30W x 24D	65	NS
BDH1521A	6 85360 15219 6	15	1	240	62.5	51,180	59-141	40H x 30W x 24D	65	NS
BDH1523A	6 85360 15221 9	15	3	240	36.3	51,180	59-141	40H x 30W x 24D	65	NS
BDH1543A	6 85360 15223 3	15	3	480	18.6	51,180	70-172	40H x 30W x 24D	65	S
BDH3043A	6 85360 15227 1	30	3	480	36.3	102,360	70-172	40H x 30W x 24D	75	NS

NOTE: BDH1021CKA includes cord & plug kit packaged inside heater carton. Status descriptions: S - Stock; NS - Non-Stock.

### ACCESSORIES

CATALOG NO.	UPC	KW	DESCRIPTION	SHIP WT. (LBS.)
DHCWM	6 85360 15212 7	-	Ceiling and wall bracket can be used on all models	20
SCS25043	6 85360 15251 6	4/3 SO	DH1521A	22
SCS10063	6 85360 15250 9	6/3 SO	DH1021A (10ft long w/plug)	18
SCS25064	6 85360 15252 3	6/4 SO	DH1583A, DH1523A, DH3043A	20
SCS25124	6 85360 15253 0	12/4 SO	DH1543A	10

### CORD & PLUG KITS

CATALOG NO.	KW	VOLTS	PHASE	AMPS	WIRE SIZE	25 FT CORD SET	LOCKING	NON-LOCKING	SHIP WT. (LBS)
BDH1021A	10	240	1	39.6	6/3	SCS10063 (10ft.)	-	INCLUDED	18
BDH1583A	15	208	3	41.8	6/4	SCS25064	LPS25064	-	20
BDH1521A	15	240	1	62.5	4/3	SCS25043	-	-	22
BDH1523A	15	240	3	36.3	6/4	SCS25064	LPS25064	NPS1550	20
BDH1543A	15	480	1	31.2	6/4	SCS25064	LPS25064	NPS1550	20
			3	18.1	12/4	SCS25124	LPS25104	-	10
BDH3043A	30	480	3	36.3	6/4	SCS25064	-	-	20

NOTE: Models designated 1 and 3 phase can be field-wired for single-phase operation.