


PRODUCT SUBMITTAL SHEET



A Marley Engineered Products Brand



Capacities
5kW and 10kW 208, 240, or 480V 3 Phase Thermostat Range: 40° - 90° F Air Movement: 500 CFM MAX

CUHS SERIES CABINET UNIT HEATERS



Job Name: _____

Location: _____

Architect: _____

Engineer: _____

Contractor: _____

Submitted By: _____

Date: _____

Submitted By:		Date:	
Approved By:		Date:	

Item	QTY	Catalog Number	Tag	Watts	Volts	PH	AMPS	Weight

ACCESSORIES			
Item	QTY	Part Number	Tag



470 Beauty Spot Road East
Bennettsville, South Carolina 29512
www.marlymep.com

Stock Cabinet Unit Heaters: Stock Models and Specifications

CATALOG NUMBER	UPC	CFM HI	CFM LOW	DIM	WT	VOLTS/PH	AMPS
CUHS93505203FFW	00685360174174	250	200		120 lbs.	208V/3Ø	14
CUHS93505203FFWD	00685360174181	250	200	35" W	120 lbs.	208V/3Ø	14
CUHS93505243FFW	00685360174198	250	200	26 3/8" H	120 lbs.	240V/3Ø	12
CUHS93505243FFWD	00685360174204	250	200	9 7/8" D	120 lbs.	240V/3Ø	12
CUHS93505483FFW	00685360174211	250	200		120 lbs.	480V/3Ø	6
CUHS93505483FFWD	00685360174228	250	200		120 lbs.	480V/3Ø	6
CUHS94510203FFW	00685360174235	500	400		120 lbs.	208V/3Ø	34
CUHS94510203FFWD	00685360174242	500	400	45" W	120 lbs.	208V/3Ø	34
CUHS94510243FFW	00685360174259	500	400	26 3/8" H	120 lbs.	240V/3Ø	15
CUHS94510243FFWD	00685360174266	500	400	9 7/8" D	120 lbs.	240V/3Ø	15
CUHS94510483FFW	00685360174273	500	400		120 lbs.	480V/3Ø	12
CUHS94510483FFWD	00685360174280	500	400		120 lbs.	480V/3Ø	12

ACCESSORIES

CATALOG NO.	DESCRIPTION	COMPATIBLE WITH	FUNCTION	SHIP WT. (LBS)
CUH935RTK	Ceiling or Wall Recess Trim Kit	CUH935	Provides a neat finish to semi-recessed or full recessed application.	3
CUH945RTK		CUH945		4
CUH935BK	Floor/Toe-Space Base Kit	CUH935	16 gauge, muted black base is recessed from the heater front and sides to provide an attractive and practical floor mounting application.	9
CUH945BK		CUH945		10
CUH935WF	Permanent, Reusable Washable Filter	CUH935	Replaces standard filter Washable filter can be cleaned and replaced.	4
CUH945WF		CUH945		6

FACTORY-INSTALLED ACCESSORIES - FFW MODELS

ACCESSORY	DESCRIPTION
BUILT-IN THERMOSTAT	Standard Built-in single stage thermostat with adjustable knob to have heater run until demand is satisfied.
MANUAL RESET	Standard Manual Reset over temperature cutout wired into control circuit. Supplied in addition to auto-reset cutout.
DEAD FRONT DISCONNECT SWITCH	Standard A three pole non-fused disconnect switch disconnects power to the heater. Design prevents entry into the control compartment until disconnect switch is turned to the OFF position.

FACTORY-INSTALLED ACCESSORIES - FFWD MODELS

ACCESSORY	DESCRIPTION
SMARTSERIES® PLUS	Standard Built-in two stage thermostat runs 2/3 elements on stage 1 and full heat for stage 2. Fan cycles on high speed only. Comes with BACnet BMS compatibility, scheduling, cooling mode (Fan-Only), and keypad lock.
MANUAL RESET	Standard Manual Reset over temperature cutout wired into control circuit. Supplied in addition to auto-reset cutout.
DEAD FRONT DISCONNECT SWITCH	Standard A three pole non-fused disconnect switch disconnects power to the heater. Design prevents entry into the control compartment until disconnect switch is turned to the OFF position.