

## LOW PROFILE SERIES



### IDEAL SPACES

- Customer Entrances
- Malls
- Stores
- Hospitals
- Restaurants
- Fast Food Windows
- Schools
- Walk-In Coolers

### COLORS

- Neutral Gray
- Charcoal Gray
- Stainless Steel
- Navajo White
- Northern White
- Statuary Bronze
- Desert Tan
- Black

- Modern contemporary design with choice of electro-static powder paint or quality stainless steel
- Patented design allows for continuous side-by-side mounting
- Cross-flow blower wheels for maximum outlet uniformity
- Easily adjustable air directional vanes
- Two-speed motor with convenient selector switch
- Pre-wired 48-in. molded cord/plug for simple installation
- Reduce infiltration of exterior air, fumes, dust and dirt
- Quick-mount mounting plate included; no template required to locate mounting screws
- Extended anodized, aluminum design compliments store interiors and public facilities
- Custom paint accents architectural sill-height heaters in vestibules and receptions areas
- Mounting heights of 7 ft. for exterior customer entrances or 8 ft. interior doors
- Act as a temperature separation device, repelling outside air while maintaining interior environment



## LOW PROFILE SERIES

### MODELS & SPECIFICATIONS

CATALOG NO.	UPC	NOZZLE WIDTH (IN)	VOLTS	AMPS	MAX VEL (FPM)	AVG VEL (FPM)	AIRFLOW (CFM)	SHIP WT. (LBS.)	MOTORS (HP)
<b>CONTEMPORARY POWDER PAINT</b>									
MLP36001115GR	6 85360 14925 7	36	120	1.3	1800	1800 / 1350	1200 / 900	32	1 @ 1/15
MLP42001110GR	6 85360 14926 4	42	120	1.6	1800	1800 / 1350	1380 / 1040	37	1 @ 1/10
MLP48001108GR	6 85360 14927 1	48	120	2.1	1800	1800 / 1350	1600 / 1210	42	1 @ 1/8
MLP60001108GR	6 85360 14945 5	60	120	2.1	1800	1800 / 1350	2060 / 1550	53	1 @ 1/8
MLP36001208GR	6 85360 14946 2	36	240	0.7	1800	1800 / 1350	1200 / 900	32	1 @ 1/8
MLP42001208GR	6 85360 14947 9	42	240	0.7	1800	1800 / 1350	1380 / 1040	37	1 @ 1/8
MLP48001206GR	6 85360 14948 6	48	240	1.0	1800	1800 / 1350	1600 / 1210	42	1 @ 1/6
MLP60001206GR	6 85360 14932 5	60	240	1.0	1800	1800 / 1350	2060 / 1550	43	1 @ 1/6
<b>CONTEMPORARY STAINLESS STEEL</b>									
MLP36001115GRSS	6 85360 14960 0	36	120	1.3	1800	1800 / 1350	1200 / 900	32	1 @ 1/15
MLP42001110GRSS	6 85360 14967 7	42	120	1.6	1800	1800 / 1350	1380 / 1040	37	1 @ 1/10
MLP48001108GRSS	6 85360 14968 4	48	120	2.1	1800	1800 / 1350	1600 / 1210	42	1 @ 1/8
MLP60001108GRSS	6 85360 14969 1	60	120	2.1	1800	1800 / 1350	2060 / 1550	53	1 @ 1/8
MLP36001208GRSS	6 85360 14970 7	36	240	0.7	1800	1800 / 1350	1200 / 900	32	1 @ 1/8
MLP42001208GRSS	6 85360 14971 4	42	240	0.7	1800	1800 / 1350	1380 / 1040	37	1 @ 1/8
MLP48001206GRSS	6 85360 14972 1	48	240	1.0	1800	1800 / 1350	1600 / 1210	42	1 @ 1/6
MLP60001206GRSS	6 85360 14973 8	60	240	1.0	1800	1800 / 1350	2060 / 1550	43	1 @ 1/6
<b>ARCHITECTURAL SERIES</b>									
MLP36001115GA	6 85360 14933 2	36	120	1.3	1800	1800 / 1350	1200 / 900	32	1 @ 1/15
MLP42001110GA	6 85360 14934 9	42	120	1.6	1800	1800 / 1350	1380 / 1040	37	1 @ 1/10
MLP48001108GA	6 85360 14935 6	48	120	2.1	1800	1800 / 1350	1600 / 1210	42	1 @ 1/8
MLP60001108GA	6 85360 14949 3	60	120	2.1	1800	1800 / 1350	2060 / 1550	53	1 @ 1/8
MLP36001208GA	6 85360 14950 9	36	240	0.7	1800	1800 / 1350	1200 / 900	32	1 @ 1/8
MLP42001208GA	6 85360 14951 6	42	240	0.7	1800	1800 / 1350	1380 / 1040	37	1 @ 1/8
MLP48001206GA	6 85360 14952 3	48	240	1.0	1800	1800 / 1350	1600 / 1210	42	1 @ 1/6
MLP60001206GA	6 85360 14940 0	60	240	1.0	1800	1800 / 1350	2060 / 1550	43	1 @ 1/6