

## LOW PROFILE SERIES



### IDEAL SPACES

- Customer Entrances
- Malls
- Stores
- Hospitals
- Restaurants
- Fast Food Windows
- Schools
- Walk-In Coolers

### COLORS

- Beige
- Charcoal Gray
- White
- Bronze
- Black



- Modern contemporary design with choice of electro-static powder paint or quality stainless steel
- Patented design allows for continuous side-by-side mounting
- Cross-flow blower wheels for maximum outlet uniformity
- Easily adjustable air directional vanes
- Two-speed motor with convenient selector switch
- Pre-wired 48-in. molded cord/plug for simple installation
- Reduce infiltration of exterior air, fumes, dust and dirt
- Quick-mount mounting plate included; no template required to locate mounting screws
- Extended anodized, aluminum design compliments store interiors and public facilities
- Custom paint accents architectural sill-height heaters in vestibules and receptions areas
- Mounting heights of 7 ft. for exterior customer entrances or 8 ft. interior doors
- Act as a temperature separation device, repelling outside air while maintaining interior environment



## LOW PROFILE SERIES

### MODELS & SPECIFICATIONS

| CATALOG NO.                         | UPC             | NOZZLE WIDTH (IN) | VOLTS | AMPS | MAX VEL (FPM) | AVG VEL (FPM) | AIRFLOW (CFM) | SHIP WT. (LBS.) | MOTORS (HP) |
|-------------------------------------|-----------------|-------------------|-------|------|---------------|---------------|---------------|-----------------|-------------|
| <b>CONTEMPORARY POWDER PAINT</b>    |                 |                   |       |      |               |               |               |                 |             |
| MLP36001115GR                       | 6 85360 14925 7 | 36                | 120   | 1.3  | 1800          | 1800 / 1350   | 1200 / 900    | 32              | 1 @ 1/15    |
| MLP42001110GR                       | 6 85360 14926 4 | 42                | 120   | 1.6  | 1800          | 1800 / 1350   | 1380 / 1040   | 37              | 1 @ 1/10    |
| MLP48001108GR                       | 6 85360 14927 1 | 48                | 120   | 2.1  | 1800          | 1800 / 1350   | 1600 / 1210   | 42              | 1 @ 1/8     |
| MLP60001108GR                       | 6 85360 14945 5 | 60                | 120   | 2.1  | 1800          | 1800 / 1350   | 2060 / 1550   | 53              | 1 @ 1/8     |
| MLP36001208GR                       | 6 85360 14946 2 | 36                | 240   | 0.7  | 1800          | 1800 / 1350   | 1200 / 900    | 32              | 1 @ 1/8     |
| MLP42001208GR                       | 6 85360 14947 9 | 42                | 240   | 0.7  | 1800          | 1800 / 1350   | 1380 / 1040   | 37              | 1 @ 1/8     |
| MLP48001206GR                       | 6 85360 14948 6 | 48                | 240   | 1.0  | 1800          | 1800 / 1350   | 1600 / 1210   | 42              | 1 @ 1/6     |
| MLP60001206GR                       | 6 85360 14932 5 | 60                | 240   | 1.0  | 1800          | 1800 / 1350   | 2060 / 1550   | 43              | 1 @ 1/6     |
| <b>CONTEMPORARY STAINLESS STEEL</b> |                 |                   |       |      |               |               |               |                 |             |
| MLP36001115GRSS                     | 6 85360 14960 0 | 36                | 120   | 1.3  | 1800          | 1800 / 1350   | 1200 / 900    | 32              | 1 @ 1/15    |
| MLP42001110GRSS                     | 6 85360 14967 7 | 42                | 120   | 1.6  | 1800          | 1800 / 1350   | 1380 / 1040   | 37              | 1 @ 1/10    |
| MLP48001108GRSS                     | 6 85360 14968 4 | 48                | 120   | 2.1  | 1800          | 1800 / 1350   | 1600 / 1210   | 42              | 1 @ 1/8     |
| MLP60001108GRSS                     | 6 85360 14969 1 | 60                | 120   | 2.1  | 1800          | 1800 / 1350   | 2060 / 1550   | 53              | 1 @ 1/8     |
| MLP36001208GRSS                     | 6 85360 14970 7 | 36                | 240   | 0.7  | 1800          | 1800 / 1350   | 1200 / 900    | 32              | 1 @ 1/8     |
| MLP42001208GRSS                     | 6 85360 14971 4 | 42                | 240   | 0.7  | 1800          | 1800 / 1350   | 1380 / 1040   | 37              | 1 @ 1/8     |
| MLP48001206GRSS                     | 6 85360 14972 1 | 48                | 240   | 1.0  | 1800          | 1800 / 1350   | 1600 / 1210   | 42              | 1 @ 1/6     |
| MLP60001206GRSS                     | 6 85360 14973 8 | 60                | 240   | 1.0  | 1800          | 1800 / 1350   | 2060 / 1550   | 43              | 1 @ 1/6     |
| <b>ARCHITECTURAL SERIES</b>         |                 |                   |       |      |               |               |               |                 |             |
| MLP36001115GA                       | 6 85360 14933 2 | 36                | 120   | 1.3  | 1800          | 1800 / 1350   | 1200 / 900    | 32              | 1 @ 1/15    |
| MLP42001110GA                       | 6 85360 14934 9 | 42                | 120   | 1.6  | 1800          | 1800 / 1350   | 1380 / 1040   | 37              | 1 @ 1/10    |
| MLP48001108GA                       | 6 85360 14935 6 | 48                | 120   | 2.1  | 1800          | 1800 / 1350   | 1600 / 1210   | 42              | 1 @ 1/8     |
| MLP60001108GA                       | 6 85360 14949 3 | 60                | 120   | 2.1  | 1800          | 1800 / 1350   | 2060 / 1550   | 53              | 1 @ 1/8     |
| MLP36001208GA                       | 6 85360 14950 9 | 36                | 240   | 0.7  | 1800          | 1800 / 1350   | 1200 / 900    | 32              | 1 @ 1/8     |
| MLP42001208GA                       | 6 85360 14951 6 | 42                | 240   | 0.7  | 1800          | 1800 / 1350   | 1380 / 1040   | 37              | 1 @ 1/8     |
| MLP48001206GA                       | 6 85360 14952 3 | 48                | 240   | 1.0  | 1800          | 1800 / 1350   | 1600 / 1210   | 42              | 1 @ 1/6     |
| MLP60001206GA                       | 6 85360 14940 0 | 60                | 240   | 1.0  | 1800          | 1800 / 1350   | 2060 / 1550   | 43              | 1 @ 1/6     |