

MFQ SERIES

COMMERCIAL FAN-FORCED WALL HEATER



IDEAL SPACES

- Offices
- Stores
- Schools
- Churches
- Hospitals
- Dormitories
- Airport Terminals
- Reception Rooms
- Lobbies
- Corridors
- Stairwells
- Conference Rooms
- Hallways
- Waiting Rooms

COLORS

- Northern White

DIMENSIONS

- Grille: 31-3/4" W x 22-3/4" H x 1-1/2" D
- Back Box: 30-1/2" W x 21-1/8" H x 3-3/4" D

TEMP RANGE

- 60°– 90°F

CFM

- 200



- Steel finned metal sheath electric heating elements with low sheath temperatures provided uniform heat and long service life
- Rugged stamped steel front cover provides a down-flow air pattern. Integral thermostat for quick installation; separate thermostat not necessary
- Thermal overheat protectors disconnect power in event of accidental blockage
- Power on/off switch for added safety during maintenance
- Permanently lubricated enclosed fan motor provides long-life and low maintenance



MFQ SERIES

COMMERCIAL FAN-FORCED WALL HEATER

MODELS & SPECIFICATIONS

CATALOG NO.	UPC	VOLTS	PHASE	WATTS	AMPS	BUILT-IN THERMOSTAT	SHIP WT. (LBS.)
MFQ6008	6 85360 04687 7	208	1	6000	28.8	Yes	50
MFQ6004	6 85360 04683 9	240	1	6000	25	Yes	50
MFQ6007	6 85360 04686 0	277	1	6000	21.7	Yes	50
MFQ6003	6 85360 04682 2	347	1	6000	17.3	Yes	50
MFQ60048	6 85360 04684 6	480	1	6000	12.5	Yes	50
MFQ6006	6 85360 04685 3	600	1	6000	10	Yes	50
MFQ8008	6 85360 04693 8	208	1	8000	38.5	Yes	50
MFQ8004	6 85360 04689 1	240	1	8000	33.3	Yes	50
MFQ8007	6 85360 04692 1	277	1	8000	28.9	Yes	50
MFQ8003	6 85360 04688 4	347	1	8000	23.1	Yes	50
MFQ80048	6 85360 04690 7	480	1	8000	16.7	Yes	50
MFQ8006	6 85360 04691 4	600	1	8000	13.3	Yes	50

ACCESSORIES

CATALOG NO.	UPC	DESCRIPTION	SHIP WT. (LBS)
MFQSM	6 85360 04679 2	Surface Mounting Frame	6
MFQS1	6 85360 04680 8	1 in. Semi-Recess Frame	5
MFQS2	6 85360 04681 5	2 in. Semi-Recess Frame	6
MFQR24	6 85360 04678 5	24V Power Relay	1
MFQR120	6 85360 04677 8	120V Power Relay	1