

SSAR ARCHITECTURAL SMARTSERIES® PROGRAMMABLE WALL HEATER



IDEAL SPACES

- Bedrooms
- Living/Family Rooms
- Basements
- Offices
- Conference Rooms
- Lobbies
- Waiting Rooms
- Entrance Ways
- Vestibules
- Restaurants
- Stairwells

COLORS

- Northern White
- Navaho White
- Aluminum
- Statuary Bronze

DIMENSIONS

- Grille: 19-1/4"H x 15-13/16"W x 2-4/5"D
- Back Box: 18-1/4"H x 14-3/8"W x 3-3/4"D

TEMP RANGE

- 40°– 99°F

CFM

- 100



- The best in contemporary design with digital touch screen LCD thermostat (5/2-day programming)
- Rugged heavy duty die cast aluminum grille, BMS compatible – Connects to Building Management Systems for optimum control
- Energy efficiency with proportional heating that automatically adjusts wattage output
- Maintains heat within 1.5 degree of set temperature (as compared to five degrees with conventional bi-metal thermostats)
- Hold function maintains constant set temperature. Use for freeze protection or vacation setting when away
- Lockout Feature – Securely maintain comfort levels
- ‘Right out of the box’ installation; fits recessed between standard studs walls with two-piece construction
- No ducting or plumbing needed means no heat loss before the heat enters the room
- Power on/off switch for added safety during maintenance

SSAR ARCHITECTURAL SMARTSERIES® PROGRAMMABLE WALL HEATER

MODELS & SPECIFICATIONS

CATALOG NO.	UPC	VOLTS	WATTS	AMPS	PHASES	BTU/HR.	SHIP WT. (LBS.)
SSAR1802	685360 156835	120	900/1800	15	1	6,142	25
SSAR4808	685360 156750	208	1440/4800	23.1	1	16,378	25
SSAR4804	685360 156781	240	1440/4800	20	1	16,378	25
SSAR4807	685360 156798	277	1440/4800	17.3	1	16,378	25

SURFACE MOUNTING FRAME ACCESSORIES

CATALOG NO.	UPC	DESCRIPTION	SHIP WT. (LBS)
HTWHSM	6 85360 15545 6	Surface Mounting Frame 15-3/8"W x 19-3/16"H x 3-3/4"D	4
HTWHS1	6 85360 15548 7	1 in. Semi-Recess Mounting Frame 15-3/8"W x 19-3/16"H x 1"D	4
HTWHS2	6 85360 15551 7	2 in. Semi-Recess Mounting Frame 15-3/8"W x 19-3/16"H x 2"D	4

NOTE: Standard grille color is Northern White. Add W (Navajo White), AL (Aluminum) or BZ (Bronze) suffix to catalog number of both the heater and mounting frame (ex. SSAR1802AL). Mounting Limitations: Do not install heater closer than 12 in. to the floor, 12 in. to an adjacent wall, 36 in. to the ceiling. Do not install heater behind towel rack or door, upside down or sideways, in the floor, in the ceiling, or in closets.

