

## CBD SERIES

### COMMERCIAL BASEBOARD HEATER



#### IDEAL SPACES

- Bedrooms
- Living/Family Rooms
- Kitchens
- Bathrooms
- Basements
- Offices
- Conference Rooms
- Hallways
- Lobbies
- Waiting Rooms

#### COLORS

- Navajo White

#### DIMENSIONS



- Ideal for basic, zoned primary/secondary heating
- No fans; convection heat minimizes air flow, reducing flow of bacteria and dust
- Commercial-grade 16-gauge cold rolled front cover and brackets allow heater to withstand rigors of commercial applications
- Steel-sheathed heating element combines the durability of a steel tubular heater with the excellent heat transfer characteristics of aluminum fins
- Junction boxes made of high-strength Lexan® to resist scratches and wear marks
- Heavy-duty steel louvered grilles discourage insertion of foreign objects
- High temperature safety limit for added protection in case of an airflow blockage
- Large, pre-wired junction boxes at each end are provided with knockouts in the rear, bottom, inside and outside
- Built-in wire-way facilitates end-to-end installation of continuous-run heaters
- Pre-notched marks for mounting guide
- UL-listed for installation flush to any wall and flat on any floor type
- Chimney-fin element designed for maximum air circulation
- Air flow directed away from walls to help prevent wall streaking



## CBD SERIES COMMERCIAL BASEBOARD HEATER

MODELS & SPECIFICATIONS							
CATALOG NO.	UPC	VOLTS	WATTS	AMPS	BTU/HR.	LENGTH (IN)	SHIP WT. (LBS)
CBD500	6 85360 01477 7	120	500	4.2	1706	28"	8
CBD508	6 85360 01480 7	208	500	2.4			
CBD504	6 85360 01478 4	240/208	500/375	2.1/1.8			
CBD507	6 85360 01479 1	277/240/208	500/375/282	1.8/1.6/1.4			
CBD750	6 85360 01481 4	120	750	6.3	2560	34"	10
CBD758	6 85360 01484 5	208	750	3.6			
CBD754	6 85360 01482 1	240/208	750/562	3.1/2.7			
CBD757	6 85360 01483 8	277/240/208	750/562/422	2.7/2.3/2.0			
CBD1000	6 85360 01462 3	120	1000	8.3	3413	46"	13
CBD1008	6 85360 01465 4	208	1000	4.8			
CBD1004	6 85360 01463 0	240/208	1000/750	4.2/3.6			
CBD1007	6 85360 01464 7	277/240/208	1000/750/562	3.6/3.1/2.7			
CBD1250	6 85360 01466 1	120	1250	10.4	4265	58"	16
CBD1258	6 85360 01469 2	208	1250	6			
CBD1254	6 85360 01467 8	240/208	1250/938	5.2/4.5			
CBD1257	6 85360 01468 5	277/240/208	1250/938/704	4.5/3.9/3.4			
CBD1500	6 85360 01470 8	120	1500	12.5	5120	70"	20
CBD1508	6 85360 01473 9	208	1500	7.2			
CBD1504	6 85360 01471 5	240/208	1500/1125	6.4/5.4			
CBD1507	6 85360 01472 2	277/240/208	1500/1125/844	5.4/4.7/4.1			
CBD2008	6 85360 01476 0	208	2000	9.6	6825	94"	27
CBD2004	6 85360 01474 6	240/208	2000/1500	8.3/7.2			
CBD2007	6 85360 01475 3	277/240/208	2000/1500/1125	7.2/6.3/5.4			

CONTROLS & ACCESSORIES			
CATALOG NO.	UPC	DESCRIPTION	SHIP WT. (LBS)
HBBT1	6 85360 03557 4	25 amp @ 120-277 VAC; Single-Pole Thermostat Snap-Action Type; Field-Installed in Junction Box	1
HBBT2	6 85360 03559 8	25 amp @ 120-277 VAC; Double-Pole Thermostat Snap-Action Type; Field-Installed in Junction Box	1
HBBT1TP	6 85360 03558 1	Same as Model HBBT1 except Tamper-Resistant	1
HBBT2TP	6 85360 03560 4	Same as Model HBBT2 except Tamper-Resistant	1
HBBAC*	6 85360 03538 3	Air Conditioner Outlet Section, 20 amps @ 208/240 VAC	2
HBBDR	6 85360 03542 0	Duplex Receptacle Section, 15 amps @ 120 VAC	2
HBBDSDR120	6 85360 14797 0	Double-Pole Disconnect Switch /120V Receptacle	3
HBBWS	6 85360 03561 1	8 in. Blank Wiring Section	1
HBBLVR0*	6 85360 03547 5	Low Voltage Relay Control Section, 25 amps @ 120 VAC	3
HBBLVR8*	6 85360 03550 5	Low Voltage Relay Control Section, 25 amps @ 208 VAC	3
HBBLVR4*	6 85360 03548 2	Low Voltage Relay Control Section, 25 amps @ 240 VAC	3
HBBADS2	6 85360 03539 0	Double-Pole Power On/Off Switch Section	2
CBDBS2*	6 85360 01453 1	2 ft. Blank Section	6
CBDBS3*	6 85360 01454 8	3 ft. Blank Section	8
CBDBS4*	6 85360 01455 5	4 ft. Blank Section	11
CBDBS5*	6 85360 01456 2	5 ft. Blank Section	14
CBDBS6*	6 85360 01457 9	6 ft. Blank Section	16
CBDBS8*	6 85360 01458 6	8 ft. Blank Section	22
CBDCIC*	6 85360 01460 9	Inside Corner	1
CBDCOC*	6 85360 01461 6	Outside Corner	1

NOTE: \*HBBAC - HBBDR - HBBLVR - HBBWS accessories add 8 in. to baseboard length. For high-altitude baseboard heater (mounted above 7,500 ft.), add suffix "H" to catalog number. 8 ft. length baseboards must be ordered in multiples of two pieces for shipment.

