ELECTRICALLY HEATED

SINGLE-PHASE ENVIRONMENTAL



IDEAL SPACES

- Vestibules
 - Stibules Reception A
- Lobbies
- Staging Areas

COLORS

- Beige
 - Ob ---- I O----
- Charcoal Gray
- White

- Reception Areas
- Waiting Rooms
- Bronze
- Black

- Heated units reduce the wind chill effect near entrances
- Heated units supplied with pre-wired heater control box for efficient installation
- Wall-mounted 24V thermostat for temperature control
- Multiple coil capacities for proper application requirements
- Heater control panel mounts in front of nozzle, below grill

MODELS & SPECIFICATIONS									
CATALOG NO.	WIDTH (IN)	WATTS	BTU/ HR	CONTROL VOLTAGE	MAX VEL (FPM)	AVG VEL (FPM)	AIRFLOW (CFM)	SHIP WT. (LBS)	MOTORS (QTY @ HP)
E36061125H	36	6,000	20,478	24	2500	2000	1620	77	1 @ 1/4
E42061125H	42				2500	1900	1795	83	1 @ 1/4
E48061125H	48				2500	1855	2000	90	1 @ 1/4
E36091125H	36	9,000	30,717	24	2500	2000	1620	77	1 @ 1/4
E42091125H	42				2500	1900	1795	85	1 @ 1/4
E48091125H	48				2500	1855	2000	90	1 @ 1/4



