



INDUSTRIAL AIR CIRCULATOR



30ACH fan head shown with optional 2430PB pole and base.



Available in two styles:

- Assembled head (motor-blade-guard) in one UPS-able carton optional mount in separate UPS-able carton.
- Assembled head (motor/blade/guard) and mount in one UPS-able box.

Fan Performance

Blade Size	Fan Head	Max Amps	CFM	
			High	Low
20"	20ACHA	1.4	3500	2900
24"	24ACH	2.2	7,000	5,900
30"	30ACH	2.5	8,200	6,200

Motor 2-speed 1/4 HP 1Ø 120 volt ball bearing totally enclosed permanently lubricated permanent split capacitor

Switch Pull chain

Cord 12' long 3 conductor SJT type

Blade Coated steel

Guard Double locking powder coat finish

Fan Head Tilt Pedestal - 10° down or 28° up
Wall mount - 40° down or 0° up

Column Adjustment 48-7/8 to 60 inches

Pedestal base 27" diameter steel dome

Column/Base Connect 5 carriage bolts

Meets OSHA standards / 1 year limited warranty.
MEP recommends the use of safety cable model 2430SC with this fan when mounted on a wall, I-beam, ceiling, or suspension mount.
Safety cable included with I-beam, ceiling and suspension mounts.

Assembled Head Ordering Summary

BLADE SIZE	FAN TYPE	ORDER NUMBER	SHIPPING WEIGHT
		FAN HEAD	HEAD
20"	Head	20ACHA	51 lbs.
24"	Head	24ACH	51 lbs.
30"	Head	30ACH	51 lbs.

Mount Ordering Summary

ORDER NUMBER	DESCRIPTION	SHIP WT
2430PB	Adjustable Pedestal	35
2430WG	Wall Mount	5
2430I	I-Beam Mount	8
2430C	Ceiling Mount	7
2430S	Suspension Mount	3

Assembled Head Uni-pack Ordering Summary

BLADE SIZE	FAN TYPE	UNIPACK ORDER#	SHIPPING WEIGHT
24"	Pedestal Fan	24ACHP	73 lbs.
24"	Wall Mount Fan	24ACHW	42 lbs.
30"	Pedestal Fan	30ACHP	78 lbs.
30"	Wall Mount	30ACHW	47 lbs.

Optional Accessories

TYPE	ORDER NUMBER
Wheel Kit	PBWK
Safety Cable	2430SC