



SPECIALTY WASHDOWN AIR CIRCULATOR

This exclusive fan is ideally suited for comfort cooling in food and beverage processing facilities, greenhouses, poultry plants, amusement parks and other high humidity or washdown environments. Fan meets UL 507 spray test requirements.



Washdown Air Circulator

Fan motor and all mounts on this page: Pedestal, Ceiling, I-Beam, Wall, and Suspension, are coated with FDA approved white epoxy (FDA 21 CFR 175.300), USDA approved for incidental food contact.

Fan Performance

Blade Size	Fan Head	Max Amps	CFM	
			High	Low
24"	LCHWD24	4.0	6,800	5,200
30"	LCHWD30	4.1	8,600	6,200

Motor	2-speed, 1/3 HP, 48-frame, single phase, 120 volt totally enclosed, permanently lubricated ball bearings, built-in thermal overload protection, permanent split capacitor motor.
Switch	5' long air actuated pendant switch
Cord	5' long 3 Conductor SJT type
Blade	Balanced aluminum
Guard	Zinc plated

Meets OSHA standards.

MEP recommends the use of safety cable model 2430SC with this fan when mounted on a wall, I-beam, ceiling mount.

Safety cable included with I-beam, ceiling and suspension mounts.

Ordering Summary

BLADE SIZE	FAN TYPE	ORDER NUMBER		SHIPPING WEIGHT	
		FAN HEAD	MOUNT	HEAD	MOUNT
24"	Head	LCHWD24	—	42 lbs.	—
24"	Pedestal	LCHWD24	LFPCBWD	42 lbs.	35 lbs.
24"	Wall Mount	LCHWD24	LWBWD	42 lbs.	5 lbs.
24"	I-Beam Mount	LCHWD24	LIBWD	42 lbs.	8 lbs.
24"	Ceiling Mount	LCHWD24	LCMWD	42 lbs.	8 lbs.
30"	Head	LCHWD30	—	49 lbs.	—
30"	Pedestal	LCHWD30	LFPCBWD	49 lbs.	35 lbs.
30"	Wall Mount	LCHWD30	LWBWD	49 lbs.	5 lbs.
30"	I-Beam Mount	LCHWD30	LIBWD	49 lbs.	8 lbs.
30"	Ceiling Mount	LCHWD30	LCMWD	49 lbs.	8 lbs.

Note: LCHWD30 Fan head does not meet UPS shipping criteria.