

COMMERCIAL DIRECT DRIVE EXHAUST FAN



LPEV



LPES

- 115V, 1Ø, totally enclosed permanently lubricated motor.
- LPEV - Venturi mounted fan - Provides optimum air flow and more rigid installation. Can be used with or without external shutter.
- LPES - Shutter mounted fan - Reduces installation time by eliminating inside and outside framing when a shutter is going to be used.

Ordering Summary

ORDER NUMBER	TYPE	BLADE SIZE	OUTSIDE DIMENSION	CFM AT 115V HIGH MED LOW	AMPS (HIGH)	SHIP WT (LBS.)
LPE12V	VENTURI FAN	12"	17-3/4" Sq.	2000 / 1600 / 1150	1.1	14
LPE16V		16"	21" Sq.	3000 / 2650 / 2250	1.1	21
LPE22V		22"	27-1/2" Sq.	4200 / — / 3700	2.1	37
LPE12S	SHUTTER FAN	12"	15" Sq.	2000 / 1600 / 1150	1.1	16
LPE16S		16"	19" Sq.	3000 / 2650 / 2250	1.1	25
LPE24S		24"	27" Sq.	5000 / — / 4200	2.2	44
LPE30S		30"	33" Sq.	7800 / — / 6600	2.5	51

COMMERCIAL BELT DRIVE EXHAUST FAN




- 115V, 1Ø, permanently lubricated, drip proof motor
 - Permanently lubricated bearings on blade shaft
 - Aluminum blade
 - Hot dipped galvanized venturi
 - Shipped fully assembled
 - 1 Year Limited Warranty
- (sleeve bearing on 24", 30", 36", ball bearing on 42")

Ordering Summary

BLADE SIZE	ORDER NUMBER	MOTOR HP	CFM (FREE AIR)	AMPS	SHIPPING WEIGHT
24"	BE24	1/2	6500	6.0	58 lbs.
30"	BE30	1/2	8300	6.0	65 lbs.
36"	BE36	1/2	10400	6.0	78 lbs.
42"	BE42	3/4	14000	9.2	92 lbs.

COMMERCIAL WALL EXHAUST SHUTTER



- Air Open — Gravity Close
- All Aluminum
- Bronze bearings
- Weather stripping for tighter seal

Ordering Summary

WALL FAN SIZE	ORDER NUMBER	OPENING REQUIRED	OVERALL DIMENSIONS	SHIPPING WT.
12"	CWS12	13" x 13"	15" x 15"	4 lbs.
16"	CWS16	17" x 17"	19" x 19"	6 lbs.
22"	CWS22	23" x 23"	25" x 25"	8 lbs.
24"	CWS24	25" x 25"	27" x 27"	11 lbs.
30"	CWS30	31" x 31"	33" x 33"	12 lbs.
36"	CWS36	37" x 37"	39" x 39"	20 lbs.
42"	CWS42	43" x 43"	45" x 45"	29 lbs.

Note: Only for use with LPE & BE Series fans.