




PROJECT _____	ENGINEER _____	SUBMITTED BY _____
DATE _____	ARCHITECT _____	
SHEET _____ OF _____	CONTRACTOR _____	



Mounts with one bolt or lag screw to work benches, steel shelving, machines, ceilings, I-Beams, wall or other surfaces.
 Fan head rotates 360 Deg. In both horizontal and vertical directions.

Specifications:

- Motor:** 115v, single phase, open drip proof, permanently lubricated sleeve bearing, 3 speed..
 12" & 14" Fans - 1/15 HP Shaded Pole. 18" & 20" Fans-1/8 HP PSC
- Blade:** Precision balanced powder paint coated steel with heavy gauge steel spider and hub.
- Guard:** Double locking powder paint coated. Meets federal OSHA standards.
- Switch:** Pull chain.
- Cord:** 10' long 3 conductor SJT.



Blade Size	Order Number	Type	High	CFM Med	Low	Amps (High)	Ship Wt.
12"	B12P	Bolt on circulator	2650	2100	1550	1.2	11 lbs.
14"	B14	Bolt on circulator	3200	2900	1600	1.3	13 lbs.
18"	B18	Bolt on circulator	5500	4600	3400	2.6	19 lbs.
18"	B18TE	Bolt on circulator	5500	4600	3400	2.6	19 lbs.
20"	B20P	Bolt on circulator	5950	4650	3500	2.6	20 lbs.

Type	Order Number	Ship Wt.
Wall Mounting Bracket	CDMW	1 lb

ITEM	QUANTITY	MARK	MODEL NUMBER	BLADE SIZE	TYPE	CFM @ 115V			AMPS (HIGH)	SHIP WT (LBS)
						HIGH	MED	LOW		