BDH SERIES

Portable Dragon Heater

PORTABLE & SPECIALTY HEATERS





Construction Sites
Food Processing
Textile Mills
Paper Mills
Printing Plants
Chemical Plants
Truck Docks
Marinas



Red






- Compact design with robust air filled tires and included plug and cord kit make this heater easy to use right out of the box
- Can be left unattended without threat of poisoning from combustion by-products associated with fuel-fired heaters. Fan only mode allows for air recirculation, fume exhaust or fresh air supply
- Redesigned control compartment adds more space and easy access to internals for fast installation and maintenance
- Designed with built-in thermostat and safety thermal cutout, thermostat selector switch, and optional ceiling/ wall bracket to heat exactly how you need
- Heavy-duty spiral fin tube metal sheath elements for uniform heat output
- > Fan-only mode for air recirculation, fume exhaust or fresh air supply
- Single- and three-phase operation
- > 10-in. pneumatic wheels
- Thermostat selector switch
- Optional ceiling/wall bracket available
- > Cord sets for power supply feed available

BDH SERIES

Portable Dragon Heater





Models & Specifications:

ITEM INFORMATION		ELECTRICAL DATA					DIMENSIONAL DATA				
	CATALOG NO.	UPC	VOLTS	PHASE	KW	BTU/HR.	AMPS	HEIGHT	WIDTH	DEPTH	SHIP WT.
•	BDH1583CKA	685360171807	208	3	15	51,180	41.8	40"	30"	24"	65 lbs
•	BDH1543CKA	685360171814	480	3	15	51,180	18.6	40"	30"	24"	65 lbs
•	BDH3043A	685360152271	480	3	30	102,360	36.3	40"	30"	24"	75 lbs
•	BDH1021CKA	685360152585	240	1	10	34,120	41.7	40"	30"	24"	65 lbs
•	BDH1521A	685360152196	240	1	15	51,180	62.5	40"	30"	24"	65 lbs
•	BDH1523A	685360152219	240	3	15	51,180	36.3	40"	30"	24"	65 lbs

SKU Legend: • = Popular Products • = Extended Offering (Contact your local Marley Sales Representative for typically associated lead times)

Optional Accessories:

CATALOG NO.		UPC	KW	DESCRIPTION	SHIP WT.
	DHCWM	685360152127	-	Ceiling and wall bracket can be used on all models	20 lbs

Optional Cord & Plug Kits:

CATALOG NO.	kW	VOLTS	PHASE	AMPS	WIRE SIZE	25 FOOT CORD	LOCKING	NON-LOCKING	SHIP WT.
BDH1021A	10	240	1	39.6	6/3	SCS10063 (10ft.)	-	Included	18 lbs
BDH1583A	15	208	3	41.8	6/4	SCS25064	LPS25064	_	20 lbs
BDH1521A	15	240	1	62.5	4/3	SCS25043	_	_	22 lbs
BDH1523A	15	240	3	36.3	6/4	SCS25064	LPS25064	NPS1550	20 lbs
DD1115.47.A	15	15 480	1	31.2	6/4	SCS25064	LPS25064	NPS1550	20 lbs
BDH1543A	15		3	18.1	12/4	SCS25124	LPS25104	_	10 lbs
BDH3043A	30	480	3	36.3	6/4	SCS25064	-	_	20 lbs

NOTE: Models designated 1 and 3 phase can be field-wired for single-phase operation.