

# CWH3000 SERIES

## Commercial Fan-Forced Large Wall Heater

## WALL HEATERS



### *Technical Specifications:*


**Temp Range:** 40°-90°F

**CFM:** 100

**Grille Gauge:** 20

### *Ideal Spaces:*

Mechanical Spaces  
Vestibules & Entrance Ways  
Lobbies, Hallways & Stairwells  
Restaurants  
Conference Rooms  
Medical Offices  
Basements  
Living/Family Room



White

- › Contemporary design combined with commercial-grade steel grille to provide comfort through optimized airflow
- › Fan-only operation for summer use
- › Built-in power on/off switch for added safety during maintenance
- › Manual reset thermal overheat protector disconnects power in the event of accidental blockage
- › Automatic fan delay eliminates cold drafts on start-up and discharges residual heat from the heater body during shut down
- › Integral double-pole thermostat allows for easy adjustment to maintain desired temperature
- › All units have a permanently lubricated enclosed fan motor, which creates long life, low maintenance, and gently distributes warmth throughout the area




Intertek



# CWH3000 SERIES

## Commercial Fan-Forced Large Wall Heater

Scan the QR code  
to access additional  
specs and features



### Models & Specifications:

ITEM INFORMATION			ELECTRICAL DATA					SHIP WT.
	CATALOG NO.	UPC	VOLTS	PHASE	WATTS	AMPS	BTU/HR.	
◆	CWH3150F	685360162386	120	1	1500	12.5	5,118	25 lbs
◆	CWH3404F*	685360162461	240	1	4000/2000	16.7/8.3	13,649/6,824	25 lbs
			208	1	3000/1500	14.5/7.2	10,236/5,118	25 lbs
◆	CWH3407F*	685360162485	277	1	4000/2000	14.5/7.2	13,649/6,824	25 lbs
			240	1	3000/1500	12.5/6.3	10,236/5,118	25 lbs
◆	CWH3408F*	685360162508	208	1	4000/2000	19.2/9.6	13,649/6,824	25 lbs
◆	CWH3504F	685360162560	240	1	4800	20	16,378	25 lbs
			208	1	3600	17.3	12,284	25 lbs
◆	CWH3507F	685360162584	277	1	4800	17.3	16,378	25 lbs
			240	1	3600	15	12,284	25 lbs
◆	CWH35083F	685360162607	208	3	4800	13.4	16,378	25 lbs
◆	CWH3508F	685360162621	208	1	4800	23.1	16,378	25 lbs
●	CWH3180F	685360162409	120	1	1800	15	6,142	25 lbs
●	CWH3307F*	685360162423	277	1	3000/1500	10.8/5.4	10,236/5,118	25 lbs
●	CWH34043F	685360162447	240	3	4000	9.7	13,649	25 lbs
●	CWH34083F	685360162508	208	3	4000	11.1	13,649	25 lbs
●	CWH35043F	685360162546	240	3	4800	11.6	16,378	25 lbs
●	CWH3153F	685360164229	347	1	1500	4.3	5,118	25 lbs
●	CWH3203F	685360164182	347	1	2000	5.8	6,824	25 lbs
●	CWH3303F	685360164267	347	1	3000	8.6	10,236	25 lbs
●	CWH3403F	685360164304	347	1	4000	11.5	13,649	25 lbs
●	CWH3503F	685360164342	347	1	4800	13.8	16,378	25 lbs
●	CWH3156F	685360164243	600	1	1500	2.5	5,118	25 lbs
●	CWH3206F	685360164205	600	1	2000	3.3	6,824	25 lbs
●	CWH3306F	685360164281	600	1	3000	5	10,236	25 lbs
●	CWH3406F	685360164328	600	1	4000	6.7	13,649	25 lbs
●	CWH3506F	685360164366	600	1	4800	8	16,378	25 lbs

SKU Legend: ◆ = Popular Products; ● = Extended Offering (Contact your local Marley Sales Representative for typically associated lead times)

\*Factory-wired for higher wattage, field-convertible to half wattage. For wall mounting - Do not install back box closer than 8 in. from floor or adjacent wall. Do not install heater behind towel rack, behind door, in floor, in closet, in ceiling or where air flow may be obstructed.

### Optional Accessories:

CATALOG NO.	UPC	DESCRIPTION	COLOR	SHIP WT.
FRAFCTPF	685360027104	Tamper-Proof Front Cover	White	2 lbs
SMFL	685360174433	Surface Mounting Frame	White	5 lbs
SMFL1	685360174440	1 in. Semi-Recessed Frame	White	2 lbs
SMFL2	685360174457	2 in. Semi-Recessed Frame	White	2 lbs
LKSFNCNW	685360160795	14-gauge Security Front Cover	White	6 lbs

### Dimensions and Clearances:

