

FRA SERIES

Commercial Fan-Forced Large Wall Heater

WALL HEATERS



Technical Specifications:


Temp Range: 40°-90°F

CFM: 100

Grille Gauge: 20

Ideal Spaces:

Mechanical Spaces
Vestibules & Entrance Ways
Lobbies, Hallways & Stairwells
Restaurants
Conference Rooms
Medical Offices
Basements
Living/Family Room



White

- › Contemporary design combined with commercial-grade steel grille to provide comfort through optimized airflow
- › Fan-only operation for summer use
- › Built-in power on/off switch for added safety during maintenance
- › Manual reset thermal overheat protector disconnects power in the event of accidental blockage
- › Automatic fan delay eliminates cold drafts on start-up and discharges residual heat from the heater body during shut down
- › Integral double-pole thermostat allows for easy adjustment to maintain desired temperature
- › All units have a permanently lubricated enclosed fan motor, which creates long life, low maintenance, and gently distributes warmth throughout the area



FRA SERIES

Commercial Fan-Forced Large Wall Heater

Scan the QR code
to access additional
specs and features



Models & Specifications:

ITEM INFORMATION			ELECTRICAL DATA					
	CATALOG NO.	UPC	VOLTS	PHASE	WATTS	AMPS	BTU/HR.	SHIP WT.
◆	FRA1512F	685360162393	120	1	1500	12.5	5,118	25 lbs
◆	FRA4024F*	685360162478	240	1	4000/2000	16.7/8.3	13,649/6,824	25 lbs
			208	1	3000/1500	14.5/7.2	10,236/5,118	25 lbs
◆	FRA4027F*	685360162492	277	1	4000/2000	14.5/7.2	13,649/6,824	25 lbs
			240	1	3000/1500	12.5/6.3	10,236/5,118	25 lbs
◆	FRA4020F*	685360162539	208	1	4000/2000	19.2/9.6	13,649/6,824	25 lbs
◆	FRA4824F	685360162577	240	1	4800	20	16,378	25 lbs
			208	1	3600	17.3	12,284	25 lbs
◆	FRA4827F	685360162591	277	1	4800	17.3	16,378	25 lbs
			240	1	3600	15	12,284	25 lbs
◆	FRA48203F	685360162614	208	3	4800	13.4	16,378	25 lbs
◆	FRA4820F	685360162638	208	1	4800	23.1	16,378	25 lbs
●	FRA1812F	685360162416	120	1	1800	15	6,142	25 lbs
●	FRA3027F*	685360162430	277	1	3000/1500	10.8/5.4	10,236/5,118	25 lbs
●	FRA40243F	685360162454	240	3	4000	9.7	13,649	25 lbs
●	FRA40203F	685360162515	208	3	4000	11.1	13,649	25 lbs
●	FRA48243F	685360162553	240	3	4800	11.6	16,378	25 lbs
●	FRA3153F	685360164236	347	1	1500	4.3	5,118	25 lbs
●	FRA3203F	685360164199	347	1	2000	5.8	6,824	25 lbs
●	FRA3303F	685360164274	347	1	3000	8.6	10,236	25 lbs
●	FRA3403F	685360164311	347	1	4000	11.5	13,649	25 lbs
●	FRA3503F	685360164359	347	1	4800	13.8	16,378	25 lbs
●	FRA3156F	685360164250	600	1	1500	2.5	5,118	25 lbs
●	FRA3206F	685360164212	600	1	2000	3.3	6,824	25 lbs
●	FRA3306F	685360164298	600	1	3000	5	10,236	25 lbs
●	FRA3406F	685360164335	600	1	4000	6.7	13,649	25 lbs
●	FRA3506F	685360164373	600	1	4800	8	16,378	25 lbs

SKU Legend: ◆ = Popular Products; ● = Extended Offering (Contact your local Marley Sales Representative for typically associated lead times)

*Factory-wired for higher wattage, field-convertible to half wattage. For wall mounting - Do not install back box closer than 8 in. from floor or adjacent wall. Do not install heater behind towel rack, behind door, in floor, in closet, in ceiling or where air flow may be obstructed.

Optional Accessories:

CATALOG NO.	UPC	DESCRIPTION	COLOR	SHIP WT.
FRAFCTPF	685360027104	Tamper-Proof Front Cover	White	2 lbs
SMFL	685360174433	Surface Mounting Frame	White	5 lbs
SMFL1	685360174440	1 in. Semi-Recessed Frame	White	2 lbs
SMFL2	685360174457	2 in. Semi-Recessed Frame	White	2 lbs
LFKSFCNW	685360160795	14-gauge Security Front Cover	White	6 lbs

Dimensions and Clearances:

