

FRC SERIES

Architectural Heavy-Duty Wall Heater

WALL HEATERS



Bronze and White

Technical Specifications:

Temp Range: 40°-90°F

CFM: 100

Grille Gauge: 18

Ideal Spaces:

Vestibules & Entrance Ways

Lobbies & Hallways

Stairwells

Restaurants


Conference Rooms

Offices

Basements

Living/Family Room

- › BMS-compatible through an optional relay
- › Contemporary bar-stock grille design provides optimized airflow
- › Manual reset thermal overheat protector disconnects power in the event of accidental blockage
- › Built-in tamper-resistant thermostat
- › All units have a permanently lubricated and enclosed fan motor, which creates long life, low maintenance, and gently distributes warmth throughout the area
- › Automatic fan delay eliminates cold drafts on start-up and discharges residual heat from the heater body during shut down
- › Power on/off switch for added safety during maintenance



White



Bronze




Intertek



FRC SERIES

Architectural Heavy-Duty Wall Heater

Scan the QR code
to access additional
specs and features



Models & Specifications:

ITEM INFORMATION			ELECTRICAL DATA					SHIP WT.
	CATALOG NO.	UPC	VOLTS	PHASE	WATTS	AMPS	BTU/HR.	
◆	FRC1512F	685360161877	120	1	1500	12.5	5,118	25 lbs
◆	FRC4307F	685360164755	277	1	3000/1500	10.8/5.4	10,236/5,118	25 lbs
◆	FRC4024F*	685360161990	208	1	3000/1500	14.4/7.2	10,236/5,118	25 lbs
			240	1	4000/2000	16.7/8.3	13,649/6,824	25 lbs
◆	FRC4027F*	685360162072	240	1	3000/1500	12.5/6.3	10,236/5,118	25 lbs
			277	1	4000/2000	14.4/7.2	13,649/6,824	25 lbs
◆	FRC4020F	685360162119	208	1	4000/2000	19.2/9.6	13,649/6,824	25 lbs
◆	FRC4824F*	685360162195	208	1	3600	17.3	12,284	25 lbs
			240	1	4800	20	16,378	25 lbs
◆	FRC4827F*	685360162270	240	1	3600	15	12,284	25 lbs
			277	1	4800	17.3	16,378	25 lbs
◆	FRC4820F	685360162317	208	1	4800	23.1	16,378	25 lbs
●	FRC4303F	685360164038	347	1	3000	8.6	10,236	25 lbs
●	FRC4306F	685360164069	600	1	3000	5	10,236	25 lbs
●	FRC4503F	685360164113	347	1	4800	13.8	16,378	25 lbs
●	FRC4506FC	685360164144	600	1	4800	8	16,378	25 lbs
●	FRC1812F	685360161891	120	1	1800	15	6,142	25 lbs
●	FRC40243F	685360162034	240	3	4000	9.6	13,649	25 lbs
●	FRC40203F	685360162157	208	3	4000	11.1	13,649	25 lbs
●	FRC45043F	685360164762	240	3	4800	11.6	16,378	25 lbs
●	FRC48203F	685360162355	208	3	4800	13.3	16,378	25 lbs

SKU Legend: ◆ = Popular Products; ● = Extended Offering (Contact your local Marley Sales Representative for typically associated lead times)

NOTE: *Factory-wired for higher wattage, field-convertible to half wattage. Units not available to be wired with remote thermostats. Standard finish is Bronze; For White, add NW suffix to catalog number.

Optional Accessories:

CATALOG NO.	UPC	DESCRIPTION	COLOR	SHIP WT.:
FRPE*	685360028224	Pneumatic/Electric switch. Factory set at 10 psig to "make" on pressure drop. May be field wired to "break" on pressure drop. Pressure set point adjustable to 30 psig. (field-installed)	—	2 lbs
FRR2 (24V)*	685360030364	Time delay relay 40-60 seconds to close when energized. Use 120V or 24V power supply from remote source (field-installed)	—	2 lbs
FRR12 (120V)*	685360030357			
FRS1PB	685360030401	1 in. deep surface mounting frame for semi-recessed installation	Bronze	2 lbs
FRS2PB	685360030425	2 in. deep surface mounting frame for semi-recessed installation	Bronze	2 lbs
FRSMPB	685360030388	Surface mounting frame for surface installations. Painted to match heater decor, 3 1/8 in. deep	Bronze	5 lbs
SMFL	685360174433	Surface Mounting Frame	White	5 lbs
SMFL1	685360174440	1 in. Semi-Recessed Frame	White	2 lbs
SMFL2	685360174457	2 in. Semi-Recessed Frame	White	2 lbs
VFKSFCNW	685360074665	14-gauge security front cover	White	6 lbs

Note: *Will accommodate pneumatic/electric or low-voltage controls commonly used with computerized energy management systems
Mounting Limitations: For wall mounting, do not install back box closer than 8 in. from floor or adjacent wall. Do not install heater behind towel rack, behind door, in floor, in closet, in ceiling or where air flow may be obstructed. All controls are concealed behind the front cover making them essentially tamper proof.

Dimensions and Clearances:

