

MSDH SERIES


High-Temp Dragon Heater

PORTABLE & SPECIALTY HEATERS



Ideal Spaces:

Construction Sites
Food Processing
Textile Mills
Paper Mills
Printing Plants
Chemical Plants
Truck Docks
Marinas




Red

- › Can be operated unattended without risk of fire or need for refueling
- › Flexible duct attachment capable to distribute heat or circulate air
- › High BTU per hour heater without the exhaust fumes or moisture associated with gas heat
- › Fan-only mode for air recirculation, fume exhaust or fresh air supply
- › Dual thermostat operation. 120V control supply and transformer with pilot light
- › Over temperature limit protects unit from low air flow conditions
- › Powder-coated, corrosion-resistant 20-gauge steel housing. 10 in. pneumatic wheels and 4 in. locking caster. Inlet and outlet flexible duct accessories available for ducting up to 165 ft.
- › Adjustable damper accessory controls outlet temperature; 1 HP motor with adjustable pulleys allowing for adjustable fan speeds
- › Temperature high limit cutout for freeze protection, removing fumes, speed drying or curing, insect control and more

MSDH SERIES

High-Temp Dragon Heater

Scan the QR code
to access additional
specs and features



Models & Specifications:

ITEM INFORMATION			ELECTRICAL DATA				DIMENSIONAL DATA			
	CATALOG NO.	UPC	VOLTS (3-PHASE)	KW	BTU/HR.	AMPS	HEIGHT	WIDTH	DEPTH	SHIP WT.
●	MSDH3043	685360149134	480	30	102,363	37.2	44"	25 3⁄8"	38 1⁄2"	150 lbs
●	MSDH3093	685360149141	600	30	102,363	30	44"	25 3⁄8"	38 1⁄2"	150 lbs
●	MSDH4843	685360149172	480	48	163,781	58.9	44"	25 3⁄8"	38 1⁄2"	160 lbs
●	MSDH4893	685360149189	600	48	163,781	47.3	44"	25 3⁄8"	38 1⁄2"	170 lbs
●	MSDH6043	685360149219	480	60	204,727	73.3	44"	25 3⁄8"	38 1⁄2"	170 lbs
●	MSDH6093	685360149226	600	60	204,727	58.9	44"	25 3⁄8"	38 1⁄2"	170 lbs

SKU Legend: ◆ = Popular Products ● = Extended Offering (Contact your local Marley Sales Representative for typically associated lead times)

Optional Accessories:

CATALOG NO.	UPC	DESCRIPTION	SHIP WT.
MSDHFX20	685360150727	20 in. Diameter Flexible Duct (25 feet)	45 lbs
MSDHDA20	685360150765	20 in. Diameter Adaptor Ring	20 lbs
MSDHSK20	685360150741	20 in. Diameter Splice Kit	40 lbs
MSDHDC	685360150789	20 in. Diameter Duct Clamp	3 lbs
MSDHAD	685360150802	Adjustable Damper	12 lbs