QCH SERIES

Ceiling-Mounted Fan-Forced Heater





Technical Specifications:

Temp Range: 45°-95°F

CFM: 65

Grille Gauge: 20

Ideal Spaces:

Basements
Offices & Lobbies
Converted Attics
Bathrooms
Workshops
Hallways & Common Areas



White

- > Dual voltage and wattage
- > Built-in power on/off switch
- > Thermal cutout to shut off heater in case of overheating
- > Easy installation with a three-piece design
- Automatic fan delay eliminates cold drafts on start-up and discharges residual heat from the heater body during shut down
- > Recessed or surface installation options available
- > Remote wall thermostat required










QCH SERIES

Ceiling-Mounted Fan-Forced Heater





Models & Specifications:

ITEM INFORMATION			ELECTRICAL DATA			
	CATALOG NO.	UPC	VOLTS	WATTS	AMPS	SHIP WT.
	QCH1101F	685360165028	120	1000	8.3	10 lbs
				500	4.7	10 lbs
	QCH1151F	685360165035	120	1500	12.5	10 lbs
				750	6.3	10 lbs
	QCH1202F	685360165042	240/208	2000/1500	8.3/7.2	10 lbs
				1000/750	4.2/3.6	10 lbs
	QCH1207F	685360165059	277/240	2000/1500	7.2/6.3	10 lbs
				1000/750	3.6/3.1	10 lbs

SKU Legend: • = Popular Products; • = Extended Offering (Contact your local Marley Sales Representative for typically associated lead times)
NOTE: Factory-wired for highest wattage, field-convertible to lower wattages.

Optional Accessories:

CATALOG NO.	UPC	DESCRIPTION	COLOR	SHIP WT.
QCHSM	685360058726	Surface mounting sleeve	White	
QCHS1	685360058733	1 in. Semi-Recessed Frame	White	2 lbs
QCHS2	685360058740	2 in. Semi-Recessed Frame	White	
QCHTBF	685360087382	T-Bar Frame Kit	White	5 lbs

NOTE: Requires two separate leads from heater to single-pole wall thermostat.

Dimensions and Clearances:

