

# RCC SERIES

## Cove Heater

# RADIANT HEATERS




### *Technical Specifications:*

**Length:** 34"-132"

**Output:** 450-1800 watts

### *Ideal Spaces:*

Offices & Retail Spaces  
Hallways & Lobbies  
Conference Rooms  
Day Care Centers  
Geriatric Facilities  
Laboratories  
Living Room & Kitchens  
Bathrooms & Basements



Textured White

- › Ideal for primary or supplemental comfort heat
- › Perfect where wall space is limited and gentle heat is desired
- › Provides clean, gentle, comfortable heat while allowing full usage of wall and floor spaces
- › No noise. No moving parts. No maintenance. No ceilings, walls or drapes to clean. No dry air
- › Extruded aluminum front panel provides a high efficiency, radiating surface
- › Coated with high temperature textured paint, unit radiates a majority of its heat energy from front surface
- › New profile and unique hanging system provide optimal heat dissipation for uniform comfort
- › Easily wall-mounted; with all parts included



# RCC SERIES

## Cove Heater

Scan the QR code  
to access additional  
specs and features



### Models & Specifications:

ITEM INFORMATION			ELECTRICAL DATA				DIMENSIONAL DATA	
CATALOG NO.	UPC		VOLTS	WATTS	BTU/HR.	AMPS	LENGTH	SHIP WT.
◆ RCC4524C	685360147192		240	450	1536	2.2	34"	4 lbs
◆ RCC6024C	685360147222		240	600	2048	2.5	47"	6 lbs
◆ RCC7524C	685360147260		240	750	2560	3.1	59"	7 lbs
◆ RCC9024C	685360147307		240	900	3072	3.7	71"	8 lbs
◆ RCC10524C	685360147451		240	1050	3583	4.4	83"	9 lbs
◆ RCC12024C	685360147376		240	1200	4095	5.0	94"	10 lbs
◆ RCC15024C	685360147406		240	1500	5120	6.2	118"	13 lbs
◆ RCC18008C	685360147420		208	1800	6142	8.7	132"	15 lbs
● RCC4512C	685360147185		120	450	1536	2.2	34"	4 lbs
● RCC4508C	685360147178		208	450	1536	2.2	34"	4 lbs
● RCC6012C	685360147215		120	600	2048	5.0	47"	6 lbs
● RCC6008C	685360147208		208	600	2048	2.9	47"	6 lbs
● RCC6027C	685360147239		277	600	2048	2.2	47"	6 lbs
● RCC7512C	685360147253		120	750	2560	6.2	59"	7 lbs
● RCC7508C	685360147246		208	750	2560	3.6	59"	7 lbs
● RCC7527C	685360147277		277	750	2560	2.7	59"	7 lbs
● RCC9012C	685360147291		120	900	3072	7.5	71"	8 lbs
● RCC9008C	685360147284		208	900	3072	4.3	71"	8 lbs
● RCC9027C	685360147314		277	900	3072	3.2	71"	8 lbs
● RCC10512C	685360147338		120	1050	3583	8.8	83"	9 lbs
● RCC10508C	685360147321		208	1050	3583	5.0	83"	9 lbs
● RCC10527C	685360147345		277	1050	3583	3.8	83"	9 lbs
● RCC12012C	685360147369		120	1200	4095	10.0	94"	10 lbs
● RCC12008C	685360147352		208	1200	4095	5.8	94"	10 lbs
● RCC12027C	685360147383		277	1200	4095	4.3	94"	10 lbs
● RCC15008C	685360147390		208	1500	5120	7.2	118"	13 lbs
● RCC15027C	685360147413		277	1500	5120	5.4	118"	13 lbs
● RCC18024C	685360147437		240	1800	6142	7.5	132"	15 lbs
● RCC18027C	685360147444		277	1800	6142	6.5	132"	15 lbs

SKU Legend: ◆ = Popular Products; ● = Extended Offering (Contact your local Marley Sales Representative for typically associated lead times)

### Optional Accessories:

CATALOG NO.	UPC	DESCRIPTION	SHIP WT.
RCCT	685360065663	Integral Thermostat: Range 45-90°F with Positive Off	1 lbs
RCCSPC	685360147666	Splice Plate Assembly	2 lbs

### Dimensions and Clearances:

