

Technical Specifications:


Temp Range: 40°–99°F

CFM: 100

Grille Gauge: 20

Ideal Spaces:

Basements
Offices
Conference Rooms
Lobbies & Waiting Rooms
Entrance Ways
Vestibules
Restaurants
Stairwells



White


- › BMS compatible—Connects to Building Management Systems for optimum control
- › Energy efficiency with proportional heating that automatically adjusts wattage output
- › Maintains heat within 1.5 degree of set temperature (as compared to five degrees with conventional bi-metal thermostats)
- › Hold function maintains constant set temperature. Use for freeze protection or vacation setting when away
- › Lockout Feature – Securely maintain comfort levels
- › No ducting or plumbing needed means no heat loss before the heat enters the room
- › SmartSeries® Digital Thermostat: 5/2-day programmability with four program periods per day
- › ‘Right out of the box’—three-piece construction—Includes back box, Element/Fan Deck and Grille
- › Fits recessed between standard stud walls or use with optional surface mounting frame (ideal for block or plaster walls)
- › Power on/off switch for added safety during maintenance



SSHOWH COMMERCIAL SMARTSERIES®

High-Output Wall Heater

Scan the QR code
to access additional
specs and features



Models & Specifications:

ITEM INFORMATION			ELECTRICAL DATA					SHIP WT.
CATALOG NO.	UPC		VOLTS	PHASES	WATTS	AMPS	BTU/HR.	
◆ SSHOWH4008	685360156705		208	1	1800/4000	8.7/19.2	13,650	26 lbs
◆ SSHOWH4004	685360156729		240	1	1800/4000	7.5/16.7	13,650	26 lbs
◆ SSHOWH4007	685360156736		277	1	1800/4000	6.5/14.4	13,650	26 lbs

SKU Legend: ◆ = Popular Products; ● = Extended Offering (Contact your local Marley Sales Representative for typically associated lead times)

Optional Accessories:

CATALOG NO.	UPC	DESCRIPTION	DESCRIPTION	SHIP WT.
HTWHSM	685360155456	Surface Mounting Frame 15 3⁄8" W x 19 3⁄16" H x 3 3⁄4" D	White	4 lbs
HTWHS1	685360155487	1 in. Semi-Recess Mounting Frame 15 3⁄8" W x 19 3⁄16" H x 1" D	White	4 lbs
HTWHS2	685360155517	2 in. Semi-Recess Mounting Frame 15 3⁄8" W x 19 3⁄16" H x 2" D	White	4 lbs

NOTE: See paint policy page for information on custom paint colors. Mounting Limitations: Do not install heater closer than 12 in. to the floor, 12 in. to an adjacent wall, 36 in. to the ceiling. Do not install heater behind towel rack or door, upside down or sideways, in the floor, in the ceiling, or in closets.

Dimensions and Clearances:

